LASER®

4294

Testeur de batterie

Facile à lire grâce aux disques flottants indiquant le niveau de charge. La compensation de température permet d'effectuer des tests à chaud ou à froid. Lecture de la densité relative et du pourcentage de charge. Plage 1,145 à 1,26 de densité relative ATTENTION : L'acide de la batterie provoque de graves brûlures. Porter des vêtements et des lunettes de protection lors de la manipulation des batteries. N.B. Rincer le testeur à l'eau après utilisation.

Additional Information

- Testeur de batterie Acide plomb
- La poire permet d'extraire le fluide et des disques flottants indiquent votre niveau de charge par cellule
- Le test peut être fait à des température hautes et basses.
- La lecture se fait à la fois en gravité et en pourcentage de charge
- Gamme de 1.145 à 1.260 sq

http://lasertools.co.uk/product/4294

TOOL CONNECTION

Distributed by The Tool Connection Ltd.
Kineton Road | Southam | Warwickshire | CV47 0DR
T | +44 (0) 1926 815 000 **F** | +44 (0) 1926 815 888
E | info@toolconnection.co.uk www.toolconnection.co.uk

LASER Kamasa Gunson Connect POWER TEC

TOOL CONNECTION
Distributed by The Tool Connection Ltd.
Kineton Road | Southam | Warwickshire | CV47 0DR
T | +44 (0) 1926 815 000 **F** | +44 (0) 1926 815 888
E | info@toolconnection.co.uk www.toolconnection.co.uk

LASER Kamasa Gunson Connect Workshop Consumables POWER TEC